
# OASIS Implant Filter Installation Guide



#### Filter Positions



- Filters for UPPER knob position go into BOTTOM filter holder.
- Filters for middle knob position go into middle filter holder.
- Filters for LOWER knob position go into TOP filter holder.



#### **Excitation Filter**



- Excitation filter goes into the back port.
- Caret on the filter points inside the filter holder.
- Fix the filter with the locking ring.
- Carefully make sure the filter is centered so that there is no gap between the locking ring and the filter ring. Air gap will leak unfiltered light to the specimen.

Caret pointing inside the filter holder



#### **Emission Filter**



- Emission filter goes into the side port.
- Caret on the filter points inside the filter holder.
- Fix the filter with the locking ring
- Carefully make sure the filter is centered so that there's no gap between the locking ring and the filter ring. Air gap will leak unwanted light into the camera.


Caret pointing inside the filter holder





Remove 4 screws securing the dichroic carrier.





Remove cover plate on top of dichroic holder by removing 8 screws.





- Place dichroic in the dichroic holder with caret on the sidewall pointing down.
- If there's no caret on the side wall, make sure the coating side is pointing down.

Caret pointing down





- Place spring frame on dichroic.
- Make sure spring frame straddles the dichroic.

Spring frame





- Place cover plate on top of dichroic holder.
- Fix the cover with 8 screws.





Correct. Dichroic cover facing inside.



Incorrect. Dichroic cover facing outside.



#### Contact Us

#### **US Office**

1241 Quarry Lane, Suite 105 Pleasanton, CA 94566 United States 925-218-1885

#### **Canada Office**

111 Railside Road, Suite 201 Toronto, ON M3A 1B2 Canada 416-840-4991

sales@mightex.com

